

Operating Instruction

# **VIBRATING SCREEN**










Henan Hongxing Heavy Machinery Co., Ltd.

### The Advantages and Application of Vibrating Screen:

Vibrating screen has such features as reliable structure, strong exciting force, high screening efficiency, low vibration noise, long service life, convenient repair and safe use, which can be

widely used for the product classification in mine, building material, transportation, energy and chemistry.



2.Exciter

- 4. Screen box
- 5. Damping spring





### The Inner Structure of Vibrating Screen:

Vibrating screen is mainly composed of screening box, exciter, hanging device and electromotor.

The electromotor drives the principal axis of the exciter to rotate through v-shaped belt, and under the centrifugal inertia force of the

unbalanced materials on the exciter, the screen box will gain vibration and it can gain different vibration amplitudes through changing the eccentric block of the exciter.

## **Characteristics:**

Processing capacity: 8-800m³/h Vibrating power: 800-970r/min Max. feeding size: 400mm

Screen size: 4-100mm Motor power: 5.5-22×2kw



## **Features**

- The strong vibration of the screen box reduces
  the phenomenon that the materials block the
  screen hole, so that the circular vibrating screen
  has high screening efficiency and production efficiency.
- 2. The circular vibrating screen has simple structure and the dismantling and changing of the screen surface is convenient.

# Technical data:

Model	Sieve layer	Sieve area (m²)	Mesh size (mm)	Max. feeding size (mm)	Processing capacity (m³/h)	Vibrating Frequency (r/min)	Double amplitude (mm)	Motor power (kw)	Sieve obliquity ( ့)	Sieve specification (mm)	Total weight (kg)	Dimensions (L×W×H) (mm)
2YK1225	2	6	4-50	400	8-60	800-970	8	5.5	20	1200×2500	3500	2930×1860×870
3YK1225	3	9	4-50	400	10-70	800-970	8	5.5	20	1200×2500	3850	3070×1860×1210
2YK1230	2	7.2	4-50	400	12-78	800-970	8	7.5	20	1200×3000	4200	$3430 \times 1860 \times 870$
3YK1230	3	10.8	4-50	400	13-80	800-970	8	7.5	20	1200×3000	4600	3570×1860×1210
2YK1237	2	8.88	4-50	400	15-86	800-970	8	7.5	20	1200×3700	4600	4050×1860×870
3YK1237	3	13.32	4-50	400	16-90	800-970	8	7.5	20	1200×3700	5200	4270×1860×1210
2YK1535	2	10.5	5-50	400	20-125	800-970	8	11	20	1500×3500	5890	$4120 \times 2210 \times 1230$
3YK1535	3	15.75	5-50	400	21-125	800-970	8	11	20	1500×3500	6700	4360×2210×1610
2YK1545	2	13.5	5-50	400	22-150	800-970	8	15	20	1500×4500	6330	5120×2210×1230
3YK1545	3	20.25	5-50	400	22-150	800-970	8	15	20	1500×4500	6800	5360×2210×1610
4YK1545	4	27	5-50	400	22-155	800-970	8	18.5	20	1500×4500	7800	5930×2210×2060
2YK1548	2	14.4	5-50	400	22.5-162	800-970	8	15	20	1500×4800	6980	5420×2210×1230
3YK1548	3	21.6	5-50	400	22.5-162	800-970	11	15	20	1500×4800	7700	5660×2210×1610
4YK1548	4	28.8	5-50	400	22.5-162	800-970	8	18.5	20	1500×4800	8700	6230×2210×2060
2YK1848	2	17.28	5-80	400	25-206	750	8	15	20	1800×4800	9080	5420×2550×1420
3YK1848	3	25.92	5-80	400	32-276	750	8	18.5	20	1800×4800	9600	5660×2550×1780
4YK1848	4	34.56	5-80	400	32-285	750	8	22	20	1800×4800	11100	6290×2550×2160
2YK1854	2	19.44	5-80	400	32-312	800-970	8	18.5	20	1800×5400	10150	5960×2550×1420
3YK1854	3	29.16	5-80	400	32-312	800-970	8	22	20	1800×5400	10840	6260×2550×1780
4YK1854	4	38.88	5-80	400	32-336	800-970	8	30	20	1800×5400	12840	6830×2550×2160
2YK2160	2	25.2	5-100	400	50-475	970	8	30	20	2100×6000	11780	6720×2840×1530
3YK2160	3	37.8	5-100	400	50-475	970	8	30	20	2100×6000	12800	7030×2840×1910
4YK2160	4	50.4	5-100	400	50-497	970	8	37	20	2100×6000	14800	$7300 \times 2840 \times 2380$
2YK2460	2	28.8	5-100	400	65-550	970	8	37	20	2400×6000	15600	7020×3140×1530
3YK2460	3	43.2	5-100	400	70-620	970	8	37	20	2400×6000	17600	7300×3140×1910
4YK2460	4	57.6	5-100	400	80-680	970	8	45	20	2400×6000	19600	$7600 \times 3140 \times 2380$
2YK2870	2	39.2	5-100	400	120-680	750	8	22×2	20	2800×7000	21200	7600×4320×1620
3YK2870	3	58.8	5-100	400	180-720	750	8	22×2	20	2800×7000	22400	7800×4320×2120
2YK3072	2	43.2	5-100	400	200-700	750	8	22×2	20	3000×7200	23600	$7800 \times 4520 \times 1750$
3YK3072	3	64.8	5-100	400	230-800	750	8	22×2	20	3000×7200	25500	8000×4520×2300





Pre-sale services: enthusiasm

We provide you with the prophase plan, process flow design and manufacturer equipment according to your special demand.

Sala corvições corvant

Send technicians to the jobsite for guiding the installation and adjustment, training operators and finishing the check and accept together with you.

After-sale services: faithfulness

To establish long term friendship, we will regularly pay return visit to customers. Supplying technique, building design, instruction, installation